

# SOFFIT LINERBOARD MINERAL WOOL (CCL)



## Description



### Product Description

CCL Soffit linerboard MW is manufactured from high density, Euroclass A1, rock mineral wool and supplied in three grades, either plain, black or white glass tissue or with a 6mm cementitious board which are bonded using a polyurethane adhesive.

Suitable for mechanical fixing in soffit applications, these boards are manufactured with no minimum order, in a 1200mm x 600mm sheet and are supplied on pallets with a weather proof covering delivered either direct to site or to stock.

### Insulation Properties

**Reaction to Fire**  
 A1 Non-Combustible

**Thickness range**  
 30mm to 200mm in 10mm increments

**Thermal Conductivity**  
 0.036 W/mK

**Compressive Strength**  
 30 kpa

\*Bonded to the mineral wool using PU adhesive

### Tissue Facing Properties\*

**Thickness**  
 0.5mm

**Air Permeability (@100Pa)**  
 3150 l/m2s

**Weight**  
 62 g/m2

### Cementitious Board Properties\*

**Reaction to Fire**  
 A1 Non-Combustible

**Thickness range**  
 6mm

**Thermal Conductivity**  
 0.19 W/mK

**Nominal Density**  
 > 1200 kg/m2



sales@concept-conversions.co.uk



01933-673100



www.concept-conversions.co.uk



Unit 13, Trinity Centre,  
 Park Farm Industrial Estate,  
 Wellingborough, Northants,  
 NN8 6ZB.

